

Name: 1237 - Initial Headlight steering wheel lamp  
 1236 - updated confirms - removed 2nd key in ignition (unconfirmed module)

Name: **lego 01 (background) - unconfirmed** **Change ID: 1027 - not for edit**

**1st Section: ignore whatever you have where the X's are and just write the hex value in the correct position: 4# Basic module BCM-BdyCM in FORSCAN**

Feature Name	Module	Address	Value change	Notes	First Reported / Confirmed
Double Horn Horn Disable	BdyCM	726-63-02	xxx*	0 = disables double horn when exiting running vehicle	D2Banover/multi
Disable driver & passenger seatbelt minder	IPC	720-02-01	xxxx	0 = Disable both 2 = Disable driver, 4 = disable passenger	LegC/multi
Disables door ajar chime	IPC	720-02-02	xxx*	0 = (off) chimes once... but not endlessly!	LegC/multi
Disable key in ignition chime	IPC	720-02-02	xxxx	*xx changed from 0 to 2	LegC/multi
Disable Auto Start Stop	PCM	740-03-01	xxxx	Start / Stop 0=Disabled 01=enabled, Angle inhibit disabled 02=enabled, Angle inhibit Disabled	D2Banover/multi
Auto Headlight	BdyCM	726-74-01	xxx*	HeadlampAutoLightOn, Clg: 00=Auto 01=Last Known	D2Banover
Power Point Timeout Duration (in seconds converted to hex)	BdyCM	726-57-01	ABCD	00=15s 15=30s 30=45s 45=60s	
Tire Size Adjustment	BdyCM	726-57-01	ABCD	00=15s 15=30s 30=45s 45=60s	
Recalibrate Speedometer	PCM	740-06-02	xxxx	Optional: to add Global Open/Close to Sync 4 Settings menu set this in APIM: 70D-00-01-xxxx xE xx	
Global Windows Open/Close	DDM	740-06-03	01xx	To roll down windows press unlock button on fob and then press again and hold	Bigmoose/multi
	DDM	741-06-03	01xx	To roll up windows press lock button on fob and then press again and hold	
	BdyCM	726-22-01	xxxx		
	BdyCM	726-22-02	xxxx		
	BdyCM	726-38-02	**xx		rednos17
	BdyCM	726-39-01	**xx		Unconfirmed
	BdyCM	726-39-01	xx**		Unconfirmed
	BdyCM	726-39-01	xxx*		Unconfirmed
	BdyCM	726-39-01	xxxx		Unconfirmed
	BdyCM	726-39-01	xxxx		Unconfirmed
	BdyCM	726-39-02	xxx*		Unconfirmed
	BdyCM	726-39-02	xxx*		Unconfirmed
	BdyCM	726-39-02	xxxx		Unconfirmed
	BdyCM	726-71-02	xxxx		Unconfirmed
	IPC	720-79-01	xxxx		Unconfirmed
	BdyCM	726-42-01	xxxx		D2Banover
Navigation in Motion	APIM	700-03-01	57xx	911 Assist will be disabled, potentially Sirius Travel Link too. First Letter of Country Code (FCC)	
Add/Change G.D.A.T. Modes	ABS	760-04-03	xxxx	2 = Baja	D2Banover/multi
	ABS	760-04-03	xxxx	3 = Rock Crawl	D2Banover/multi
	ABS	760-04-03	xxxx	A = Mud/Fltn	D2Banover/multi
	ABS	760-04-03	xxxx	B = Sport Mode	D2Banover/multi
Screen - Visual Design Variants (VDV)	APIM	700-03-01	xxxx	05=Unclsd Sync 4 13 2" (Dashboard) 06=Unclsd Sync 4 13 2" (Dashboard) 0A=12" Landscape (Dashboard)	Unconfirmed
Daytime running lights - after writing vehicle must be in drive to see new state (doesn't work in park)	BdyCM	726-42-01	**xx	01=DR, Lamp: Clg: Usage: Clg: 00=Not Used 01=DR, Only 02=DR, Position 03=Fixed DR, Position 04=Fixed Position Only 05=Position Only 06=Stop Turn	D2Banover/multi
	BdyCM	726-42-01	xx**	01=DR, Lamp: Clg: Usage: Clg: 00=Not Used 01=DR, Only 02=DR, Position 03=Fixed DR, Position 04=Fixed Position Only 05=Position Only 06=Stop Turn	D2Banover/multi
Lane Change Blink Number	S66M	704-06-06	xxxx		D2Banover
Window Reset Procedure:	Manual Process			Window needing reset steps: 1) open window and hold button down for 3-4 seconds 2) close window and hold button down for 3-4 seconds Repeat 2 more times on same window	mattn54/multi
Keyfob Panic Button	BdyCM	726-62-01	*xx	0=disabled, 1=2 clicks, 2=one click (default)	rednos17/multi
Steering Wheel Temperature	ECM	Clg: Wheel Temperature Level		Temperature set in degrees C	tor14E

GOAT by Trim

Base	Norm.	Ec.	Sprt	Wet	Sand	Mud	Rock	Blgn
Base	Yes	Yes	Yes	Yes	Yes	No	No	No
Big Bend	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Black Diamond	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Outer Banks	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Red Rock	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
Wild Track	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
First Ed.	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes

GOAT

	Drive	Trac. Ctr	FR Lock	RR Lock	Throttle	Steering	Trans.	Sway Disc	Grill air dam	Exhaust
Normal	2H	Normal	Open	Open	Normal	Normal	Normal	Connect	Open	Closed
Economy	2H	Normal	Open	Open	Soft	Soft	Soft	Connect	Closed	Closed
Sport	2H/4A	Off	Open	Open	Aggressive	Tight	Hard	Connect	Open	Open
Weather	2H/4A	Extra	Open	Open	Soft	Soft	Soft	Connect	Open	Closed
Sand	4H/4L	Extra	Lock	Lock	Normal	Soft	Soft	Connect	Open	Open
Mud	4H	Off	Lock	Lock	Normal	Soft	Soft	Connect	Open	Open
Rock	4L	Off	Lock	Lock	Soft	Tight	N/A	Disconnect	Open	Open
Blgn	4H	Off	Open	Open	Aggressive	Tight	Hard	Connect	Open	Open

\*E Equipped

GOAT by Trim

	Norm.	Eco.	Sprt	Wet	Sand	Mud	Rock	Baja
<b>Base</b>	Yes	Yes	Yes	Yes	Yes	No	No	No
<b>Big Bend</b>	Yes	Yes	Yes	Yes	Yes	Yes	No	No
<b>Black Diamond</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
<b>Outer Banks</b>	Yes	Yes	Yes	Yes	Yes	Yes	No	No
<b>Bad Lands</b>	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
<b>Wild Track</b>	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes
<b>First Ed.</b>	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes

GOAT

	Drive	Trac. Cnt	FR Lock	RR Lock	Throttle	Steering	Trans.	Sway Disc	Grill air dam	Exhaust
<b>Normal</b>	2H	Normal	Open	Open	Normal	Normal	Normal*	Connect.	Open	Closed
<b>Economy</b>	2H	Normal	Open	Open	Soft	Soft	Soft*	Connect.	Closed	Closed
<b>Sport</b>	2H/ 4A*	Off	Open	Open	Aggressive	Tight	Hard*	Connect.	Open	Open
<b>Weather</b>	2H/ 4A*	Extra	Open	Open	Soft	Soft	Soft*	Connect.	Open	Closed
<b>Sand</b>	4H/ 4A*	Extra	Lock	Lock	Normal	Soft	Soft*	Connect.	Open	Open
<b>Mud</b>	4H	Off	Lock	Lock	Normal	Soft	Soft*	Connect.	Open	Open
<b>Rock</b>	4L	Off	Lock	Lock	Soft	Tight	N/A	Discon.	Open	Open
<b>Baja</b>	4H	Off	Open	Open	Aggressive	Tight	Hard*	Connect.	Open	Open

\*If Equipped